



STAIN REMOVAL DETERGENT FOR QUARTZ AGGLOMERATES READY TO USE

Specific cleaner for quartz, removes colored stains and intense organic dirt.



WATER BASE



EXTRAORDINARY
MAINTENANCE

TECHNICAL CHARACTERISTICS

Ready-to-use product, ideal for deep cleaning quartz agglomerates.

HOW TO APPLY IT

Tools

Cloth, sponge, floor polisher, wet vacuum.



Mode

Spray the solution on the surface, let it act for 5-10 minutes (for specific stains see the table), then clean and rinse with a damp sponge cloth. In case you use the single disc machine, when you clean the floor, we suggest to remove the residues with a wet vacuum cleaner and then rinse with clean water. The product may change the appearance of some plastics and alkali-sensitive surfaces. Avoid contact with surfaces treated with wax as it could be removed. After washing, once the surface is clean and dry it is advisable to apply a protective coating for Quarzo Tenax.

If the surface is treated for the first time it is advisable to assess the effect and the adherence of the tile on a sample or a hidden corner. Close the container after use.

Attention: Do not exceed the maximum contact time of 30 minutes, as specified in the table.

STAINS AND DILUTION	CONTACT TIMES
Fruits stains and coloured stains; Algae and organic dirt	30'
Cosmetic residues, lipstick, shoes polish, coffe, red wine, blood, soap	da 10' a 30'
Wax residues and wax candle residues	30'
Frash paint and emulsion of polymers	30'
Signs of rubber, marks of shoes	30'
Fingers Print	3'
Markers	da 20' a 30'

WHERE TO APPLY IT

AGGLOMERATE



PLUS/ADVANTAGES

- DEGREASE THE SURFACES THOROUGHLY
- CLEANS FINGERPRINTS TYPICAL OF THIS MATERIAL
- REMOVES ORGANIC STAINS EVEN COLORED
- REMOVES MARKERS
- EFFECTIVENESS AND RESPECT OF THE MATERIAL ACCORDING TO THE TESTS PERFORMED (UNI EN 8298-14)

TECHNICAL DATA

Density at 25 °C gr/ml 1.005

Appearance liquid

Standard colour light yellow

pH 9.5, alkaline

COVERAGE

Product to be used as such, pure

FOR DEEP CLEANING 50-70 m²/lt
538-753 sq.ft.

TO REMOVE STAINS apply product abundantly until the stains are completely covered 30-40 m²/lt
323-430 sq.ft.

Information contained in this data sheet is up-to-date and correct as at the date of issue. As TENAX cannot control or anticipate the conditions under which this product may be used, each user should review the information in specific context of the planned use. TENAX will not be responsible for damages of any nature resulting from the use or reliance upon the information contained in this data sheet. TENAX is not responsible for incorrect use of the product.



[Click or scan
for more info
and video](#)



MADE in ITALY

AT YOUR DISPOSAL
TENAX.IT

PACKAGING

0,75-1-5 litres.

HOW TO STORE IT

Under normal use and work conditions, when stored far from heat sources, humidity and direct sunlight, the product is guaranteed for 24 months. Accurately close the pack after use.

WARNINGS

Keep out of reach of children. Avoid contact with skin and eyes. Do not mix with other substances. If the surface is treated for the first time, we recommend that you assess the effect and the adherence of the material on a sample or hidden corner.

LEGISLATION

Before use, please read the instructions on the safety data sheet and the notes found on the container.

CLOSE THE CONTAINER AFTER USE.

FOR PROFESSIONAL USE ONLY.